




---

 PRODUCT-DETAILS

# KSE3125TPN

## KSE3125TPN Enclosed Switch Disconnecter



□□□□	
□□□□	KSE3125TPN
□□□□	2CMA144588R1000
□□□□□(EAN)	7392696445887
□□□□	KSE3125TPN Enclosed Switch Disconnecter
□□□□	Encl. Switch Disconnecter, 3-p. 415V AC23 90A, 45kW. Aluminium enclosure. IP65. Black Round handle. Interlocked cover. The dye casted aluminum alloy (silumin) enclosure is extremely rigid, and well suited for harsh environment. The surface is polyester coated and well protected from corrosion. Installation is made easy, thanks to the easy access to terminals, screwed cover and with the grommet type of glands included (IP54). The cover is interlocked, and handle padlockable with two padlocks. The handle can also be padlocked in position, by removing two small plastic bits. N and PE terminals included.

---

**Material Compliance**

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC340076D0201
RoHS	1SCC340075D0201
RoHS	Following EU Directive 2011/65/EU
Toxic Substances Control Act - TSCA	1SCC340095D0201

□□□□	
□□□□	1 piece
□□□□	85363030
□□	Bulgaria (BG)

**Popular Downloads**

□□□□□□□□	1SCC340015C0201
□□□□□	1SCC340166M0205
□□□□	OTFK2231614RM40.stp

□□	
□□□□	160 mm
□□□□	230 mm
□□□□	118 mm
□□□□	1.83 kg

□□□□	
□□□□ AC-22A (I ) e	(380 ... 415 V) 125 A (500 V) 125 A (690 V) 125 A
□□□□ AC-23A (I ) e	(380 ... 415 V) 90 A (500 V) 70 A (690 V) 50 A
□□□□ AC-23A (P e)	(380 ... 415 V) 45 kW (500 V) 45 kW (690 V) 45 kW
□□□□ (I the)	Fully Enclosed 125 A
□□□□ (U i)	acc. to IEC/EN 60664-1 750 V
□□□□	Main Circuit 750 V
□□□□□□□□ (I cm)	(690 V AC) 3.6 kA
□□□□□□□□ (I cw)	for 1 s 2.5 kA
□□□□□□□□ (I nc)	16.5 kA
Handle Color	Black
□□□□	Round handle
□□	IEC 60947-1, -3
□□	3
Neutral Type	Fixed neutral
□□□□□□□□	Screw Clamp 10 ... 70 mm <sup>2</sup> Screw Clamp / PE Terminal 1pc, 6 ... 35 mm <sup>2</sup>
□□□□	10 ... 70 mm <sup>2</sup>
□□□□	20 mm
□□□□□□	Main Circuit Hexagon 4
□□□□	Top and/or Bottom
□□□□	2xM40 / 2xM40+M16
Impact Resistance Rating	Housing IK09
□□□□	Aluminium
Maximum Mounted Auxiliary Contacts	2 NO, 2 NC
□□□□□□□□	0 NO, 0 NC
□□□□NC□□	0
□□□□NO□□	0
□□□□	Main Circuit 6 N·m

UL/CSA

	20 mm
	Main Circuit Hexagon 4
	Main Circuit 6 N-m

- CE	1SCC340062D2702
------	-----------------

	box 1 piece
	170 mm
	240 mm
	150 mm
	1.83 kg
EAN	7392696445887

	Q
	2CMT005069
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
UNSPSC	39122205
IDEA (IGCC)	5166 >> Safety switch
e	V11.1 : 27371403
WEEE	5. Small Equipment (No External Dimension More Than 50 cm)

→ Enclosed Switch-Disconnectors

