



PRODUCT-DETAILS

B24 111-200

, Energy meter'Steel', IR port, Three-phase, 6 A



General Information

Extended Product Type	B24 111-200
Product ID	2CMA100809R1000
ABB Type Designation	B24 111-200
EAN	7392696008099
Catalog Description	, Energy meter'Steel', IR port, Three-phase, 6 A
Long Description	Advanced compact DIN-rail meter with an easy to read back lighted display. The meter is intended for use in the commercial or residential buildings etc. The meter can be used in 3 or 4 wire systems. The meter has several instrumentation values, 25 possible alarms and event logs. Three phase transformer connected for active energy. One output for pulses or alarm etc. Accuracy class 1.0 (or B for MID meters). The meters is IEC approved + EAC approved and verified.

Eco Transparency

Environmental Product Declaration - EPD	9AKK108467A4138
---	-----------------

Technical

Standards	IEC 62052-11, IEC 62053-21, GOST 31818.11-2012, GOST 31819.21-2012
Function	Electricity meter
Sub-Function	Steel
Rated Voltage (U_r)	3x220-240 V
Rated Current (I_n)	1 A Maximum 6 A
Current Rating	6 A
Rated Frequency (f)	50 / 60 Hz 0.721 W
Communication Interface	IR port
Accuracy	Active Energy Class $\pm 1\%$
Measuring Instrument Conformity	GOST
Meter Tariff Rating	One-Tariff
Pulse Output Rate	1-999999
Number of Poles	3 or 4
Number of Phases	Three-phase
Number of Counter Positions	7
Number of Digital In/Outputs	1 DO
Meter Type	Transformer connected
Mounting Type	DIN-Rail
Pulse Output Type	Electrical
Type of Indicator	Digital
Enclosure Material	Polycarbonate in transparent front glass. Glass reinforced polycarbonate in bottom case and upper case. Polycarbonate in terminal cover.
Connecting Capacity Main Circuit	0.5 ... 10 mm ²

Material Compliance

RoHS Information	2CMC485007
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
RoHS Date	2012-36
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Air Temperature	Operation -40 ... 70 °C
Degree of Protection	IP20
Environmental Information	2CMC485003D0001

Dimensions

Width in Number of Modular Spacings	4
Product Net Width	70 mm
Product Net Height	26.5 mm

Product Net Depth / Length	65 mm
Product Net Weight	0.25 kg
Size	97X70X65

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.32 kg

Certificates and Declarations

Declaration of Conformity - CE	No declaration needed
--------------------------------	-----------------------

Installation

Instructions and Manuals	2CMC485019M0201
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	2CMC485003M0201
-----------------------------------	-----------------

Classifications

ETIM 8	EC001506 - Kilowatt-hour meter
ETIM 9	EC001506 - Kilowatt-hour meter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	90283019
eClass	V11.0 : 27142316
Object Classification Code	P

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Energy Efficiency Devices → Energy Meters

